PRESS RELEASE

Source: Tokyo Institute of Technology, Public Relations Section

For immediate release: November 27, 2019

Subject line: Thermo-chemical power generation integrated with forced convection cooling to create a self-sustaining liquid cooling system

(Tokyo, November 27) Scientists at Tokyo Institute of Technology (Tokyo Tech) combine forced convection cooling with thermo-electrochemical energy conversion to create a selfsustaining liquid cooling system. A liquid electrolyte is circulated through a cell to cool a hot object, and the reversible chemical reaction in the cell generates a higher electric power than the hydrodynamic pump work required to drive the liquid through the cell. This technology resolves the longstanding unaddressed issue of the loss of free energy component of the thermal energy that accompanies forced convection cooling, a process that has widespread use in the modern world.

Active cooling is crucial in most modern technologies, ranging from microprocessors in data centers to turbines and engines. Forced convection cooling, which circulates a coolant fluid over the surface of a hot object, is effective for meeting such cooling requirements but demands a pumping power to send the coolant through the heat generating section. However, active cooling — fast removal of a large quantity of thermal energy in the heat source under a large temperature difference — promptly destroys the *free-energy component of the thermal energy*, which is an energy portion that can be converted to an electric work. This issue concomitant with forced convection cooling has remained unaddressed despite the widespread use of forced convection cooling in the current world.

One specific method for converting wasted heat — the heat that doesn't need to be actively removed — into electrical energy through liquid chemical reactions has been studied for several decades. This method, called *thermo-electrochemical conversion*, involves the submergence of two electrodes held at different temperatures in a liquid electrolyte encased in a closed vessel, where a reversible reduction–oxidation ("redox") reaction occurs. This reaction generates an electric current through an external circuit. Research on thermo-electrochemical conversion has been mostly carried out for static fluids.

In this study, a team of researchers from Tokyo Institute of Technology integrated thermoelectrochemical conversion with forced convection cooling to partly recover the aforementioned free-energy portion, presently lost during forced-convection cooling, in the form of electric power. In the cell developed by these researchers, the electrolyte liquid is flown as a coolant between two parallel electrodes, one of which is a heat-releasing object to be cooled. The redox reaction occurring in the cell generates electricity; this electricity can be used to drive the coolant flow through the cell. This work delves into uncharted territory, as the concept and feasibility of self-sustaining liquid-cooling system have not been previously demonstrated. The researchers carried out detailed studies to elucidate how the cooling and power generation works in this type of forced-flow thermo-electrochemical system. These novel findings are expected to provide a basic strategy for scaled-up future applications. *"Although the prototype cell developed in this study was small and thus the power generation performance was limited, this technology has much scope for improvement through optimizing the geometry of the liquid channel, electrode material, and the redox chemicals,"* remarks Prof. Yoichi Murakami, the principle investigator of this project.

Through further studies, this concept proposed by the researchers can hopefully find its application in near future, providing a new technological platform for forced convection cooling. *"Through this approach, we can partially recover the free energy portion of the thermal energy currently lost during forced convection cooling, and this acquired electric power can be used for pumping the coolant in forced convection cooling,"* concludes Prof. Murakami.

Proposed Concept: Integration of Thermo-electrochemical Conversion with Forced Convection Cooling to Create a Self-sustaining Cooling System



Reference

Authors:	Yutaka Ikeda, Kazuki Fukui, and Yoichi Murakami
Title of original	Integration of Thermo-electrochemical Conversion into Forced Convection
paper:	Cooling
Journal:	Physical Chemistry Chemical Physics (Royal Society of Chemistry)
DOI:	<u>10.1039/c9cp05028k</u> (Open Access for free)
Corresponding	<u>arXiv:1908.08646</u> (August 23, 2019)
preprint	
Affiliations:	School of Engineering, Tokyo Institute of Technology

*Corresponding author's email: <u>murakami.y.af@m.titech.ac.jp</u>

Contact Kazuhide Hasegawa Public Relations Section, Tokyo Institute of Technology <u>E-mail.media@jim.titech.ac.jp</u> +81-3-5734-2975

About Tokyo Institute of Technology

Tokyo Institute of Technology stands at the forefront of research and higher education as the leading university for science and technology in Japan. Tokyo Tech researchers excel in a variety of fields, such as material science, biology, computer science and physics. Founded in 1881, Tokyo Tech has grown to host 10,000 undergraduate and graduate students who become principled leaders of their fields and some of the most sought-after scientists and engineers at top companies. Embodying the Japanese philosophy of "monotsukuri," meaning technical ingenuity and innovation, the Tokyo Tech community strives to make significant contributions to society through high-impact research. Website: http://www.titech.ac.jp/english/