PRESS RELEASE

Source: Tokyo Institute of Technology Japan Science and Technology Agency (JST)

For immediate release: January 28, 2019

Subject line: Putting that free energy around you to good use with minuscule energy harvesters

(Tokyo, January 28) Scientists at Tokyo Institute of Technology developed a micro-electromechanical energy harvester that allows for more flexibility in design, which is crucial for future IoT applications.



Lead author Daisuke Yamane from Tokyo Tech (middle) with co-authors Hiroshi Toshiyoshi (left) and Hiroaki Honma (right) from University of Tokyo

Nowadays, it would be hard to not notice that electronic devices have become incredibly small. The use of miniature sensors in the upcoming Internet of Things (IoT) era could enable us to develop applications that were only seen in science fiction. However, microelectronic devices still require power to run, and energy-harvesting micro-electromechanical systems (MEMS) can be used so that these minuscule contraptions can run on ambient energy, such as that coming from mechanical vibrations.

As depicted in Fig. 1, conventional MEMS energy harvesters use an electret (the electrical equivalent of a permanent magnet; it has permanent charge stored in it) placed in an MEMS tunable capacitor, which has a moving electrode that is pushed by ambient forces, inducing the movement of charges. Unfortunately, this design is very constrained because the fabrication processes for both the electret and the MEMS components have to be compatible. Therefore, a team of scientists, including Assistant Professor Daisuke Yamane from Tokyo Institute of Technology, proposed a new MEMS electret-based energy harvester that consists of two separate chips: one for the MEMS tunable capacitor, and one containing an electret and dielectric material to form another capacitor (Fig. 1). "This allows us to physically separate MEMS structures and electrets for the first time," states Yamane.



MEMS Vibratory Electret Energy Harvester

Figure 1. Conventional versus proposed MEMS energy harvesters

Unlike conventional electret-based MEMS energy harvesters, which contain the entire system in a single chip, the proposed design methodology involves having the electret and the MEMS tunable capacitor in different chips, loosening up design constraints.

The energy-harvesting mechanism of the device is shown in Fig. 2. The capacitance of the electret circuit is fixed (C_{fix}), whereas that of the MEMS tunable capacitor (C_M) changes according to the stretching of the spring (caused by external vibrations). When C_M becomes higher than C_{fix} , a movement of charges is induced and the tunable capacitor gains charge. Likewise, when C_{fix} is higher, charges move in the opposite direction and the capacitor in the electret circuit gains charge.



Figure 2. Principle of operation of the proposed energy harvester

When the capacity of the tunable capacitor is higher than that of the electret circuit, a movement of charges is induced in one direction. Likewise, when the situation is reversed, a movement of charges is induced in the opposite direction.

These movements of charges represent electrical power that can be exploited. The left side of Fig. 3 shows pictures of the fabricated chips and a simplified diagram, and the right side shows that voltage can be effectively generated. "The proposed method can be a promising way to enhance the design and fabrication flexibility of both MEMS structures and electrets," concludes Yamane. Loosening up design constraints expands the limits for engineers and will accelerate the onset of the IoT era so that we can reap its benefits.



Figure 3. Pictures of the system and measured voltage output

To the left, pictures of the designed system are shown; the comb-like structure of the MEMS tunable capacitor can be appreciated. To the right, the measured voltage output demonstrates that mechanical vibratory energy can be effectively harvested.

Ref	eren	ce
-----	------	----

Authors:	Daisuke Yamane, ^{1,2} * Hiroaki Honma ³ and Hiroshi Toshiyoshi ³
Title of original	A MEMS Vibratory Energy Harvester Charged by an Off-chip Electret
paper:	
Conference:	<u>MEMS 2019</u> (The 32nd International Conference on Micro Electro Mechanical Systems)

Affiliations: ¹Institute of Innovative Research, Tokyo Institute of Technology ²Precursory Research for Embryonic Science and Technology (PRESTO), JST ³Institute of Industrial Science, The University of Tokyo

*Corresponding author's email: yamane.d.aa@m.titech.ac.jp

Contacts

Emiko Kawaguchi Public Relations Section Tokyo Institute of Technology <u>media@jim.titech.ac.jp</u> +81-3-5734-2975

Tsuyoshi Nakamura Department of Innovation Research Japan Science and Technology Agency (JST) <u>presto@jst.go.jp</u> +81-3-3512-3531

About Tokyo Institute of Technology

Tokyo Tech stands at the forefront of research and higher education as the leading university for science and technology in Japan. Tokyo Tech researchers excel in fields ranging from materials science to biology, computer science, and physics. Founded in 1881, Tokyo Tech hosts over 10,000 undergraduate and graduate students per year, who develop into scientific leaders and some of the most sought-after engineers in industry. Embodying the Japanese philosophy of "monotsukuri," meaning "technical ingenuity and innovation," the Tokyo Tech community strives to contribute to society through high-impact research. www.titech.ac.jp/english/

About Japan Science and Technology Agency (JST)

JST is an organization that leads Japan's science and technology (S&T) development as an innovation navigator. We aim to contribute to the lives of people and the achievement of a sustainable society by promoting S&T for the purpose of opening up opportunities in innovation. Since its foundation, JST's many outstanding achievements accomplished in collaboration with the government, universities, the industrial sector and public have been earned global recognition.

www.jst.go.jp/EN/index.html